





OHS-CHR-1605
Single Function 150X150mm Square Shape Maze Overhead Shower, Stainless
Steel
43.80 LPM @ 3 bar
By using flow regulators + Brass Housing (Product should be ordered with suffix as
GA-6.0 LPM, GB-8.0 LPM, & GC-12.0 LPM @ 3.0 Bar pressure) one can regulate
the flow rate.
0.5 Bar - 3.0 Bar
0.5 bai - 5.0 bai
Wall Mounting
Single Function
Brass Rod as per IS:319-1989
Cu (56.0-59.0), Pb (2.0-3.5), Fe (0.0-0.35), Total Impurity (0.0-0.7), Zn (Remainder)
Cal (30.0-33.0), FB (2.0-3.3), Fe (0.0-0.33), Total impulity (0.0-0.7), 211 (Nemainder)
Carbon 0.0-0.08, Iron Remainder (AISI 304)
learners of the member (1 and 50 1)
ABS: Specific Gravity (g/cm ²) 1.06-1.10, Melt Mass Flow Rate (g/10 min.) 20-26,
Rockwell Hardness 95-115, DTUL @ 66 psi (0.45 MPa) (0C) 78-102
Advanced Rubit - Lime scale deposits stick to the shower face can be easily
rubbed off by hand or flannel.
276017
Salt Spray (350 hrs + Validated)
Adhesion (Pass)
Antique Bronze (ABR), Antique Copper (ACR), Black Chrome (BCH), Black Matt (BLM), Gold Dust (GDS), Auric Gold (GLD), Graphite (GRF), Stainless Steel Finish

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.