



Product CodeHSH-BLM-1715DescriptionSingle Function 105mm dia Round Shape Hand Shower with Air Effect (with Face Plate Black Matt)Flow Rate9.92 LPM @ 3 barFlow regulatorBy using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM & GB-8.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.Recommended Water Pressure1.0 Bar - 3.0 BarSpray ModesSingle FunctionABS Specification in PercentageSpecific Gravity g/cm2 (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)Technology"Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel."Finish"Salt Spray (350 hrs + Validated)		
Black Matt)  Flow Rate 9.92 LPM @ 3 bar  Flow regulator By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM & GB-8.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.  Recommended Water Pressure 1.0 Bar - 3.0 Bar  Spray Modes Single Function  ABS Specification in Percentage Specific Gravity g/cm2 (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)  "Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel."  Finish "Salt Spray (350 hrs + Validated)	Product Code	HSH-BLM-1715
By using flow regulators + Brass Housing (Product should be ordered with suffix as GA-6.0 LPM & GB-8.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.  Recommended Water Pressure  1.0 Bar - 3.0 Bar  Spray Modes  Single Function  ABS Specification in Percentage  Specific Gravity g/cm2 (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)  "Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel."  Finish  "Salt Spray (350 hrs + Validated)	Description	·
LPM & GB-8.0 LPM @ 3.0 Bar pressure) one can regulate the flow rate.    Recommended Water Pressure	Flow Rate	9.92 LPM @ 3 bar
Pressure  Spray Modes  Single Function  ABS Specification in Percentage  Specific Gravity g/cm2 (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)  "Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel."  Finish  "Salt Spray (350 hrs + Validated)	Flow regulator	
ABS Specification in Percentage  Specific Gravity g/cm2 (1.06-1.10), Melt Mass Flow Rate g/10 min. (20-26), Rockwell Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)  "Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel."  Finish  "Salt Spray (350 hrs + Validated)		1.0 Bar - 3.0 Bar
Percentage  Hardness (95-115), DTUL @ 66 psi /0.45 MPa 0C (78-102)  "Unique Air Technology - Air is mixed in the water through a built-in air mixer which is a part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower  Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel."  Finish  "Salt Spray (350 hrs + Validated)	Spray Modes	Single Function
part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower  Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by hand or flannel."  Finish  Finish  Salt Spray (350 hrs + Validated)	•	
FINISN	Technology	part of the shower. This leads to lighter voluminous drops which reduce water consumption by 30% and also assuring a soft and refreshing shower  Advanced Rubit - Lime scale deposits stick to the shower face can be easily rubbed off by
Adhesion (Pass)"	Finish	"Salt Spray (350 hrs + Validated) Adhesion (Pass)"
Available Finishing BLACK MATT (BLM)	Available Finishing	BLACK MATT (BLM)

DISCLAIMER: Our every effort has been made to ensure factual accuracy, the information presented subject to changes due to requirements in different sites, markets and/ or countries. 10% variation in flow rate may be possible. Jaquar reserves the right to make the necessary amendments at any time without prior notice.