

CNS-WHT-551SSPP

SPECIFICATION DATA SHEET

DRODUCT DETAILS

FRODUCT DETAILS							
Manufacturer :	Jaquar	Туре:	EWC (S trap)				
Range	Continental	Flush valves	Regular, Dual & I Flush advantages				
Colour:	White	Material:	Ceramic - Vitreous China				
Outlet	Vertical	BOM doc.NO.	JSW/01/2018/0056				

External diameter of outlet hole Ø 100 +5 -2 mm Technical Details:


Horizontal distance between the Bowl eage and the centre line of the waste outlet hole ≤ 100 mm


ARTICLE NAME: BOWL FOR EXTENDED WALL HUNG WC






TECHNICAL DIMENSIONS







ALL DIMENSIONS ARE IN MM. BACK VIEW (TOLERANCE ± 5 MM)

PRODUCT DIMENSIONS				USP			
Length (mm)	Width (mm)	Height (mm)	Net weight (kg)				
350	475	390	13.04	Box rim , concealed trap, Anti germ glaze			
ACCESSORIES PROVIDED							
PP Soft Close Seat cover				CNS-WHT-105S			
Outlet gasket				ZPS-BLK-GK02			
Floor fixing screw				ZPS-SNS-FB01			
CARE AND CLEANING GUIDELINES							

- * Vitreous china sanitary ware products are fragile in nature and need to be handled with care (to avoid personal injury) at all times during its storage, handling, installation and use thereafter.
- ★ The product is heavy and it is recommended that two persons hold it while it is being fixed.
- \bigstar Carefully inspect the new product for damage before installation.
- \bigstar Risk of product damage. Over tightening may cause breakage or chipping of vitreous china.
- ★ Risk of external leakage. Do not lift or rock the bowl after placement.
- ★ Always test your cleaning solution on an inconspicuous area on the product before applying it to the entire surface.
- ★ Do not allow cleaners to sit or soak on the product.
- ★ Use a soft, dampened sponge or cloth to clean. Never use abrasive material like a bristle brush or scouring pad.
- ★ Wipe surfaces clean and rinse completely with water immediately after applying cleaners.
- ★ Clean Chrome, stainless steel surfaces once a week. Do not use cleaners containing chloride on chrome, stainless steel. If used, rinse the surface immediately to prevent corrosion.

★ Wherever chrome plating is used on the products, use only warm water to clean and then dry with a soft cloth.

CERTIFICATION

Compliance: IS 2556.2:2004, IS 2556.1:1994, EN 997:2012+A1/CE All technical dimensions are in accordance to British standards, Bureau of Indian Standards









Prepared By		Controlled By	Verified By	Approved By		
Designer		Quality control	Product Manager	Sanitaryware Head		
Date						
Revision/Version	1		Plotter Updated on Month	21-Aug	Year	2019